



## Intense zoom. Incredible simplicity.

Get closer to the action with the Kodak EasyShare Z650 zoom digital camera. It features a 10X Schneider-Kreuznach Variogon optical zoom lens, so you can zero in with exceptional crispness. And with its built-in picture-enhancing features, you can get stunning shots, on the spot. The Z650. Get close. Really close.

### Beautiful picture quality

- Zoom in to get crisp shots with the professional-quality 10X Schneider-Kreuznach Variogon optical zoom lens
- Create unbelievable-quality prints up to 50 x 76 cm (20" x 30") with 6.1 MP
- Capture breathtaking color under a variety of lighting conditions with the exclusive Kodak color science chip

### Auto and manual creative controls

- Get a great shot time after time with picture-enhancing features: on-camera cropping, digital red-eye reduction, and histogram
- Be in control with advanced manual settings and custom controls, including selectable aperture priority, shutter priority, and full manual mode
- Easily access its scene and color modes (17 scene, 5 color)
- Capture life in motion with continuous VGA (640 x 480) video using less memory with MPEG-4 compression
- Capture the moment as it happens with first and last burst mode

### Sharing made simple

- View your pictures on the 5 cm (2.0") indoor/outdoor color display
- Print, e-mail, and organize your photos with just one touch of our exclusive Share button
- Use Favorites to keep your special pictures close
- Keep on shooting with 32 MB of internal memory\* and SD/MMC expansion card slot
- Works with optional Kodak EasyShare photo printer 500, Kodak EasyShare printer dock plus series 3, Kodak EasyShare printer dock series 3, and Kodak EasyShare camera dock series 3†

Just press



# Kodak EasyShare Z650 zoom digital camera

## Making digital even simpler

The best part about your digital camera? Your pictures. So when you print your pictures – whether you choose to do it at home, online, or right where you shop – look to Kodak. Because when you trust your prints to Kodak, you can be sure you're getting quality that's truly exceptional and pictures that will last. Learn more about printing choices at [www.kodak.com/go/simplypictures](http://www.kodak.com/go/simplypictures)



### Standard features

CCD resolution – 1/2.5" type (6.36 megapixels)  
Image resolution – 6.1 megapixels (2832 x 2128 pixels)  
Picture quality  
6.0 MP – best (prints up to 20" x 30")  
5.3 MP – best 3:2 (optimized ratio for 4" x 6 prints)  
4.0 MP – better (prints up to 20" x 30")  
3.1 MP – better (prints up to 11" x 14")  
1.7 MP – good (small prints)  
Still format JPEG/EXIF v 2.21  
Lens – 10X optical zoom (35 mm equivalent: 38-380 mm)  
Advanced digital zoom – 5X  
Aperture – f/2.8-f/8 (wide), f/3.7-f/8 (tele)  
Shutter speed – automatic: 1/8-1/1700 sec.;  
manual 8-1/1000 sec.  
Viewfinder – electronic, high-resolution 201K pixels  
LCD – 2.0" (5.0 cm) indoor/outdoor color display

### Creative performance features

Still capture modes – auto, program, aperture priority, shutter priority, manual and burst  
Scene modes – children, party, beach, flower, fireworks, snow, backlight, close-up, night portrait, landscape, night landscape, museum/manner, text, self portrait, portrait sport and night  
Color modes – high color, low color, natural color, black and white, sepia  
Burst modes – first burst: 2 fps, up to 4 pictures; last burst: 2 fps, saves last 3 pictures  
Click to capture – 0.3 sec. (preview on)  
Shot to shot – 1.7 sec.  
Video capture – continuous video with audio and playback  
Video resolution – VGA (640x480 pixels) at 11 fps; QVGA (320x240 pixels) at 20 fps  
Video length – continuous up to 80 min. based on memory capacity; or 5, 15, 30 sec. clips  
Video format – QuickTime MOV (MPEG-4 compression)  
Auto-focus – assist lamp for low-light focus  
Auto-focus control – single AF, continuous AF, multi-zone, center-zone  
Focus range  
Normal wide – 0.6 m (2 ft.) to infinity  
Normal tele – 2 m (6.6 ft.) to infinity  
Close-up wide – 0.12-0.7 m (4.7-27.6 in.)  
Close-up tele – 1.2-2.1 m (3.9-6.9 ft.)  
Sensitivity – ISO equivalent 80-160 (automatic) and 80,100, 200, 400, 800\*\* (selectable)  
White balance – auto, daylight, tungsten, fluorescent and open shade  
Exposure metering – auto: TTL-AE; selectable: multi-pattern, center-weighted, center spot  
Manual exposure control – aperture priority AE: f/2.8-f/8 at wide, f/3.7-f/8 at tele; shutter priority AE: 8-1/2000 sec. at wide  
Long time exposure – 8 sec.  
Exposure compensation – +/-2.0 EV in 1/3 EV step increments

### Effortless operation

Built-in flash – auto, red-eye reduction, fill, off  
Flash range  
wide – 0.6-4.9 m (2-16.1 ft.) at ISO 168  
tele – 2.0-3.7 m (6.6-12.1 ft.) at ISO 168  
Flash compensation – +/-1.0 EV in 1/3 EV steps  
Review modes – album, slideshow, multi-up, copy, protect, image storage, Share button to print, e-mail  
Auto-picture rotation  
Software – Kodak EasyShare software  
Self-timer – 2 or 10 seconds, or 2 shot  
Editing – on-camera cropping, digital red-eye reduction  
Favorites – slide show, multi-up, remove Favorites, cancel print  
Share mode – print, print all, e-mail, Favorites, setup menu  
Dedicated buttons – menu, review, Share, dedicated delete, 5-way switch, mode dial (auto, sport, portrait, night, scene PASM, movie) Favorites, off, on, shutter, timer/burst, close-up/landscape, flash settings  
Histogram – histogram display on live view, quick view and review  
Storage – 32 MB internal memory\*, SD/MMC card expansion slot

### Additional features

Dock compatibility – works with optional Kodak EasyShare photo printer 500, Kodak EasyShare printer dock plus series 3, Kodak EasyShare printer dock series 3, and Kodak EasyShare camera dock series 3†  
Connectivity – I/O interface – NTSC or PAL, selectable via dock/printer dock interface, digital (USB 2.0) connector  
ImageLink print system compatible  
PictBridge enabled  
Power options – optional Kodak EasyShare docks with Ni-MH rechargeable battery pack; 2 AA lithium batteries or 1 CRV3 lithium battery; 3 volt DC  
Accessory lens thread – 55 mm  
Lens protection – lens cap  
Tripod mount – 1/4 in. standard  
Weight – without batteries: 287 g (10.1 oz.)  
Dimensions – WxHxD: 97.8x77.5x72.6 mm (3.8x3.1x2.9 in.)  
Warranty – one year

### Minimum system requirements

Windows 98, 98SE, ME, 2000 SP1, or XP OS  
233 MHz processor or greater (300 MHz recommended for XP)  
64 MB RAM (128 MB for XP)  
Internet Explorer 5.01 or higher  
PowerMac or PowerBook G3, G4, G5; iMac; eMac; or iBook computer  
Macintosh OS X 10.2.3-10.2.8, 10.3 or greater  
128 MB RAM for OS X (64 MB RAM for OS 8.6/9.x)

### Minimum hardware requirements

200 MB hard drive disk space available  
CD-ROM drive  
Available USB port  
Color monitor, 800x600 display resolution, 16-bit minimum

### Package contents

Kodak EasyShare Z650 zoom digital camera  
Kodak lithium digital camera battery CRV3  
USB and AV cables  
Lens cap  
Lens adapter  
Carrying strap  
Kodak EasyShare software  
Getting started kit  
Custom camera insert for optional Kodak EasyShare camera and printer docks

### Ordering information

Kodak EasyShare Z650 zoom digital camera  
(U.S. and Canada) ..... xxx xxxx

### Recommended accessories

Kodak EasyShare printer dock series 3 ..... xxx xxxx  
Kodak EasyShare printer dock plus series 3 ..... xxx xxxx  
Kodak EasyShare photo printer 500 ..... xxx xxxx  
Kodak color cartridge and photo paper kit ..... xxx xxxx  
Kodak EasyShare camera dock series 3 ..... xxx xxxx  
Schneider-Kreuznach Xenar 0.7x wide-angle lens ..... xxx xxxx  
Schneider-Kreuznach Xenar 1.4x telephoto lens ..... xxx xxxx  
B&W circular polarizer ..... xxx xxxx  
B&W neutral density filter ..... xxx xxxx  
Kodak SD memory cards –  
512 MB ..... xxx xxxx  
1 GB ..... xxx xxxx  
Kodak Li-Ion rechargeable digital camera battery KLIC-5001 ..... xxx xxxx  
Kodak Li-Ion rapid battery charger kit K5000-C ..... xxx xxxx  
Kodak 8-in-1 card reader ..... xxx xxxx  
Kodak performance series digital camera case ..... xxx xxxx  
Kodak EasyShare picture viewer ..... xxx xxxx  
Kodak digital camera tripod ..... xxx xxxx

\*32 MB internal memory/28 MB available for picture storage (1 MB equals one million bytes).

\*\*ISO 800 available only at 1.8 MP setting.

†Compatibility identified by this yellow symbol. (Kodak dock adapter kit D-22 required to enable compatibility with Kodak EasyShare printer dock plus, printer dock, printer dock 6000 and camera dock 6000.)



For more information on the Kodak EasyShare Z650 zoom digital camera, visit [www.kodak.com/go/easyshare](http://www.kodak.com/go/easyshare)