



12 Megapixels	5X Optical Zoom	2.5" LCD
------------------	--------------------	-------------

Kodak EasyShare Z1285

Zoom Digital Camera

HD quality at a price that clicks.

Great moments deserve great pictures. The KODAK EASYSHARE Z1285 Zoom Digital Camera lets you relive your favorite memories in brilliant HD quality. Take crisp pictures and videos and share them with your friends and family. And best of all, it's affordable, making picture-taking easier than ever on you, and your wallet.

- Take stunning HD pictures and videos and view them on your HDTV with the optional KODAK EASYSHARE HDTV Dock.
- 12 MP and 5X SCHNEIDER-KREUZNACH VARIOGON optical zoom lens for unbelievable quality prints up to 30"x 40".
- Capture the details in low light conditions and fast action situations with high ISO (up to 3200*).
- Reduce blur caused by subject movement or fast-action situations with blur reduction technology.
- Get creative with advanced settings including program and full manual mode (P/M).
- Make better, brighter, more vivid pictures on-camera, using KODAK PERFECT TOUCH Technology.
- Capture stunning shots with ease—smart scene mode automatically selects the best scene mode.

View and share your pictures and videos in stunning HD quality



12 MP for unbelievable quality prints up to 30"x 40"

High ISO (up to 3200*)



Experience it. Kodak

Kodak EasyShare Z1285

Zoom Digital Camera

Standard features

Sensor type	1/1.72" CCD
CCD total pixels	12.4 MP (4088 x 3040)
Effective pixels	12.1 MP (4011 x 3011, including ring pixels)
Lens	35 - 175 mm (35 mm equiv.), f/2.8 - f/5.1 Schneider-Kreuznach Variogon lens
Zoom	5X optical, 5X continuous advanced digital zoom
Image stabilizer	digital
Shutter speed	1/2 - 1/2000 sec. in smart scene mode and 8 - 1/1000 sec. in manual mode
LCD	6.4 cm (2.5") (115 K pixels) indoor/outdoor color display
Storage	64 MB** internal memory, SDHC/SD card expansion slot

Auto focus

Type	TTL imager AF system
Focus modes	normal AF, macro AF, infinity AF, manual
Focus range	normal (wide): 0.6 m (2') - infinity, (tele): 0.9 m (3') - infinity; macro (wide): 0.2 - 0.7 m (7.9" - 3'); (tele): 0.5 - 1.0 m (1.6' - 3.3'); landscape (wide, tele) - 10 m (32.8') - infinity
Auto focus zones	continuous AF, single AF, TTL multi-zone AF (5 zones), (4) center zone AF

Exposure control

ISO sensitivity	auto, 100, 200, 400, 800, 1600, 3200*
Metering	multi-pattern, center-weighted, spot
Compensation	± 2.0 EV with 1/3 EV steps
Bracketing	± 2.0 EV with 1/3 steps, 3 images
AE lock	when shutter button is pressed
Histogram	yes
White balance	auto, daylight, tungsten, fluorescent, open shade

Flash

Range	wide: 0.6 - 5.9 m (2' - 19.4') (ISO 400); tele: 0.6 - 3.2 m (2' - 10.5') (ISO 400)
Modes	auto, red-eye reduction, fill, off

Shooting specifications

Drive modes	single shot, first burst (1.7 fps, 3 frames), last burst (1.7 fps, last 3 frames), self-timer 10 sec., delay shutter, 2 sec., two-shot self-timer
Shooting modes	smart scene, SCN, P (program), M (manual), video capture, high ISO, digital image stabilization
Scene modes	portrait, sports, landscape, close-up, night portrait, night landscape, snow, beach, text/document, fireworks, flower, manner/museum, self-portrait, children, backlight, panning, candlelight, sunset, panorama stitch
Click to capture	<0.3 sec.
Shot to shot	<1.6 sec.

Still capture

Still format	JPEG/EXIF v 2.21
Picture size (recorded pixels)	12.0 MP (4:3) (4000 x 3000) 10.7 MP (3:2) (4000 x 2664) 9.0 MP (16:9) (4000 x 2256) 6.0 MP (4:3) (2832 x 2128) 3.1 MP (4:3) (2048 x 1536) 2.2 MP (3:2) (1800 x 1200) 2.1 MP (16:9) (1920 x 1080) 1.2 MP (4:3) (1280 x 960)
Color modes	high color, natural color (default), low color, sepia, black and white
Sharpness	high, normal, low
Review menu	single image display (default), fast scroll, magnify: normal, 2X - 8X in 1X increments, view by (all, date, album, image storage), album, Kodak Perfect Touch technology, crop, edit video, slide show, multi-up, copy, protect, setup menu, play movie, delete, Share/print, e-mail, Favorite, picture/video info

Editing

Editing	on-camera cropping, Kodak Perfect Touch technology, voice annotation
---------	--

Video capture

Format	QuickTime video format MPEG4
Quality	HD (1280 x 720) at 30 fps, VGA (640 x 480) at 30 fps, QVGA (320 x 240) at 30 fps
Length	continuous up to 80 min. or 2 GB based on memory capacity
Review options	play, rewind, pause, fast-forward, forward and rewind by frame, multi-up, slide show, view by date, view by album, view by image storage

Editing

Editing	make a picture from video (1, 4, 9, 16-up), trim, video bookmarking
---------	---

Customization

Custom settings	LCD brightness, power saving, image storage, album, capture frame grid, orientation sensor, sound, volume, date and time, auto power off, video out, language
-----------------	---

Sharing

Favorites	slide show, multi-up, setup menu, direct Favorites
Share	print, print all, e-mail, Favorites, cancel print

Physical specifications

I/O interface	USB 2.0 high speed connector with A/V output, exclusive Kodak camera dock
Power	optional Kodak EasyShare docks with Kodak Li-Ion rechargeable battery pack; 2AA batteries (Ni-MH, Lithium or, Ni-Mn)
Dedicated buttons	power, shutter, mode dial, flash, self/burst, zoom, delete, disp/info, 5-way, menu, review, Share
Tripod mount	1/4" standard
Dimensions	W x H x D: 89.5 x 64.5 x 31.6 mm (3.5"x 2.5"x 1.2")
Weight	without batteries and memory card: 161 g (5.7 oz.)

Compatibility

Dock compatibility	works with optional Kodak EasyShare G610 printer dock, Kodak EasyShare HDTV dock, and Kodak EasyShare camera dock series 3
Direct print	Kodak EasyShare photo printer 500, ImageLink print system compatible, PictBridge enabled
Software	works with Kodak EasyShare software

Service and support

Warranty	one year
----------	----------

Minimum system requirements***

Windows	Windows XP or higher, 600 MHz processor or greater; Internet Explorer 6.0 or higher
Macintosh	Macintosh OS X 10.3 or higher

Minimum hardware requirements***

Minimum hardware requirements***	128 MB RAM; 200 MB hard drive disk space available; CD-ROM drive, available USB port; color monitor, 800x600 display resolution, 16-bit minimum
----------------------------------	---

Package contents

Package contents	Kodak EasyShare Z1285 zoom digital camera
	Kodak oxy-alkaline digital camera batteries - AA
	USB cable
	Wrist strap
	Kodak EasyShare software
	Getting started guide
	Custom camera insert for optional Kodak EasyShare camera and printer docks

Ordering information

Ordering information	Kodak EasyShare Z1285 zoom digital cameraxxx xxxx
----------------------	---

Recommended accessories

Recommended accessories	Kodak EasyShare G610 printer dockxxx xxxx
	Kodak EasyShare HDTV dockxxx xxxx
	Kodak color cartridge & photo paper kit/G200xxx xxxx
	Kodak EasyShare camera dock series 3xxx xxxx
	Kodak oxy-alkaline digital camera batteries AAxxx xxxx
	Kodak SD high performance memory cards 2 GBxxx xxxx
	1 GBxxx xxxx
	Kodak graphite black camera bag/mediumxxx xxxx
	Kodak graphite black camera bag/largexxx xxxx
	Kodak digital camera tripodxxx xxxx
	Kodak travel kitxxx xxxx

For more information on the Kodak EasyShare Z1285 zoom digital camera, visit www.kodak.com/go/easysshare

*ISO 3200 available at 3.1 MP and less in P/M modes.
**64 MB internal memory/58 MB available for picture storage (1 MB equals one million bytes).
***For optimal viewing of HD videos, visit www.kodak.com/go/hdsysreq for additional information.

