



CLOSURE NOTIFICATION

Product Type: Plastic Tight Head (PTH)

TIGHT HEAD PLASTIC DRUM CLOSURE NOTIFICATION

This method of closure should be used to ensure that your containers have been closed in the same manner as when they were initially tested to comply with the requirements of the US Department of Transportation in CFR 49 Part 178.2(c)(1) Performance Transportation of Dangerous Goods in the United States.

Your product may adversely affect container materials, or closing devices. Greif Bros. Corporation has advised the US Department of Transportation that the product compatibility is the customer(s)/filler(s) responsibility.

These instructions for container closure are based upon the closure methods used to enable these containers to pass the qualification test for registration to the United Nations.

The closure recommendations do not take into account any hazards present in your facility, or the handling, filling or shipping methods used by your facility.

Containers with obvious damage or deterioration should not be filled or shipped.

Listed below are the closure size and type needed per container size. To order replacement closure(s), contact Linda Murray, Kodak Photochemicals at (585) 722-1187.

55 Gallon Drum	NPS 2" Closure and BTR (Buttress) 2" Closure
30 Gallon Drum	NPS 2" Closure and BTR (Buttress) 2" Closure

To Close:

1. Openings in tight head plastic drums **MUST BE FITTED WITH** plugs bearing NPS and/or BTR threads.
 2. Plugs must be fitted with gaskets appropriate to the plug size and design.
 3. Plugs must be placed into the appropriate openings and tightened to a torque level of 20 FT-LBS for 2" fittings and 9 FT-LBS for all 3/4" fittings.
-

If you have questions regarding the Closure Notification, contact Kodak's Worldwide Hazardous Materials Transportation Hotline at (585) 722-2400.

