

Kodak EasyShare

zoom digital camera
and camera dock 6000

DX6490



Amazing print quality

- Get really close with its 10X (38-380 mm) professional-quality optical Schneider-Kreuznach Variogon™ zoom lens
- Features the exclusive Kodak Color Science image processing chip derived from the same color technology that goes into our Professional series cameras
- Print stunning pictures up to 20" x 30" with 4.0MP
- Get bright pictures – even in low light – with high-speed, low-light capable precision auto-focus

Versatile performance

- Fine-tune for the shot you want with advanced creative and manual controls and an external flash synch
- Use the high-resolution electronic viewfinder to see your shots just the way you shot them, or view your pictures through the large 2.2" LCD
- Be ready for just about any situation with easily accessible scene modes

Sophisticated simplicity

- Includes a Kodak EasyShare Li-Ion battery and camera dock 6000 for one-touch-simple transferring, e-mailing, printing, and recharging
- Capture moments in motion with video and audio
- See your vertical shots vertically with auto picture rotation
- Compatible with Kodak EasyShare printer dock 6000

The Kodak EasyShare DX6490 zoom digital camera is your key to self-expression. Built to give you endless creative versatility and effortless control, the DX6490 supplies advanced professional-quality features such as a powerful 10X (38-380 mm) optical Schneider-Kreuznach Variogon zoom lens and the most vividly lifelike color possible, thanks to our exclusive Kodak Color Science image processing chip and over 80 years of color science engineering. The results are simply stunning. Razor-sharp focus. Inspired compositions. Dramatic depth. An intimate glimpse into reality, or a surreal look at the abstract. Whatever your eye sees the DX6490 can capture. And with a touch of our exclusive Share button, you can show your vision to the world.

Kodak EasyShare
system

Shoot. Touch. Share. With the Kodak EasyShare system, sharing is simple. Just place your Kodak EasyShare digital camera into the dock, touch the button, and your pictures are automatically sent to your computer. Now you're ready to e-mail pictures and share great-looking prints with the world.

Just press



10X OPTICAL ZOOM
3X ADVANCED DIGITAL
30X TOTAL ZOOM

4.0
MEGAPIXEL

PRINTS UP TO
20x30
50x70cm
POSTER SIZE

EVF
ELECTRONIC
VIEWFINDER

INDOOR/OUTDOOR
DISPLAY

PASM
MANUAL
MODES

AF
HIGH SPEED
LOW LIGHT AF

MULTI-ZONE
AUTO FOCUS

ISO 800
HIGH SPEED
SENSITIVITY

AUTO PICTURE
ROTATION

MATRIX
METERING

SHARE
BUTTON

16 MB
INTERNAL
MEMORY

COMPATIBLE WITH
6000 SERIES DOCKS



DX6490

Making digital even simpler

The Kodak EasyShare camera dock 6000 makes it simple to transfer pictures from camera to computer in one touch. It even recharges your Kodak camera's battery pack – in less than three hours. Want more? The optional Kodak EasyShare printer dock 6000 does everything the Kodak EasyShare camera dock 6000 does, plus it provides the simplest way to print real borderless 4" x 6" Kodak photos – with or without a computer.

Standard Features

CCD resolution – 4.23 megapixel (2408x1758 pixels)
Image resolution – 4.0 megapixel (2304x1728 pixels)

Image quality

4.0MP – best (print, enlargement 20" x 30")
3.5MP – best (optimized ratio for 4"x6": prints, 3:2)
2.1MP – better (small print)
1.1MP – good (e-mail)

Lens

10X optical zoom, 6.3-63.2 mm (35 mm equivalent:
38-380 mm)
3.0X Advanced Digital Zoom
30X total zoom

Auto-focus – multi-zone, center-spot

Focus distance –

wide std: 0.6m (2 ft.) to infinity
tele std: 2m (6.6 ft.) to infinity
wide/tele infinity: 20m (65.6 ft.) to infinity

LCD – 2.2" (5.6 cm), 153k pixels, Indoor/Outdoor display

Aperture – f/2.8-8.0 (wide), f/3.7-8.0 (tele)

Shutter speed – 16-1/1700 sec.

White balance – auto, daylight, tungsten, fluorescent

ISO equivalent – auto: 80-160

selectable: 80/100/200/400/800 (800 1.1MP quality only)

Built-in flash – auto, red-eye, fill, off
external flash synch available

Flash range

wide: 0.5-4.9m (1.6-16.1 ft.)
tele: 2.0-3.7m (6.6-12.1 ft.)

Viewfinder – electronic, 1.1 cm (.44 in.) 180K pixels

Self-timer – 10 seconds

Performance Features

Scene modes – auto, sport, night, landscape, close-up, portrait, program (aperture priority, shutter priority, manual)

Photo settings – color, black and white, sepia, saturated, neutral, sharpness (sharp, standard, soft)

Close-up mode

wide: 12-70 cm (4.7-27.6 in.)
tele: 120-210 cm (47.2-82.7 in.)

Burst mode – 3 fps up to 6 pictures

Exposure metering – TTL-AE (menu selectable:
multi-pattern, center weighted, center spot)

Exposure compensation – +/-2.0 EV with 0.33 EV step increments

Exposure control – programmed AE aperture priority, shutter priority, manual

Click to capture – 0.65 sec.

Shot to shot – <2 sec.

Movie mode – continuous digital video with audio capture, audio playback on camera

Movie resolution – 320x240 at 20 fps

Movie length – up to 80 minutes, limited by capacity of external memory card

Ease of Use Features

Capture always ready

Auto picture rotation

Dedicated buttons – Share, delete, flash, menu, review, burst/timer, information, close-up/landscape

Review options – 2X or 4X magnify, picture info, slide show, multi-up, fast scroll, protect, albums

Video – NTSC, PAL (user-selectable)

Software – Kodak EasyShare software v3.0

Dock compatibility – Kodak EasyShare camera dock 6000 and Kodak EasyShare printer dock 6000

Additional Features

Storage – 16MB internal memory and MMC/SD expansion card slot

Power options – DC in jack on side of camera for 5V adapter; Kodak EasyShare Li-ion rechargeable battery (KLIC 5000 or KLIC 5501), Kodak EasyShare camera dock 6000 and Kodak EasyShare printer dock 6000

Image recording format – Still – JPEG/EXIF v2.2, Video – Quicktime

Interface – USB 2.0 compatible, Kodak EasyShare camera 6000 and Kodak EasyShare printer dock 6000 compatible

Lens protection – lens cap tethered to camera body

Tripod mount – 1/4 in. standard

Weight – without batteries: 337 g (11.9 oz.)

Dimensions – WxHxD: 99.6x79.9x81.2 mm (3.9x3.1x3.2 in.)

Warranty – one year

System Requirements

Windows:

Windows 98, 98SE, 2000, ME, or XP OS

233 MHz processor or greater

64MB RAM (128MB RAM for Windows XP)

100MB hard drive disk space available

CD-ROM drive

Available USB port

Color monitor, 800x600 pixels (16-bit or 24-bit recommended)

Macintosh:

PowerPC based Macintosh computer

Macintosh OS X (OS 8.6/9.x – Share button

functions not supported – OS X is recommended for full functionality)

128MB RAM for OS X (64MB RAM for OS 8.6/9.x)

200MB hard drive disk space available

CD-ROM drive

Available USB port

Color monitor, 800x600 pixels (thousands or millions of colors recommended)

Package Contents

Kodak EasyShare DX6490 zoom digital camera and Kodak EasyShare camera dock 6000

Audio/video cable

USB cable

Neck strap

Lens cap with tether

Kodak EasyShare Li-ion rechargeable battery

Kodak EasyShare software CD with interactive software tutorial

Welcome kit and user's guide

Custom camera insert for Kodak EasyShare 6000 series camera and printer docks

Ordering Information

Kodak EasyShare DX6490 zoom digital camera and Kodak EasyShare camera dock 6000

000 0000 (US)

000 0000 (Canada)

Need #s

Recommended Accessories

Kodak EasyShare printer dock 6000 – 823 7448

Kodak color cartridge and photo paper kit – 123 1349

Kodak 6-in-1 card reader – 879 0792

Kodak Li-ion rechargeable battery – 1700 mAh – 106 4062

Kodak Li-ion rapid battery charger – 808 0673

Kodak Digital Camera Tripod – 806 2135

Kodak SD memory cards, 256 MB – 813 2219

Kodak Performance Series Digital Camera Case – 138 2084

For more information on the Kodak EasyShare DX6490 zoom digital camera and camera dock 6000, visit www.kodak.com/go/easysshare

©Eastman Kodak Company, 2003. Kodak, EasyShare, the Share button, and Share Moments. Share Life, are trademarks of Eastman Kodak Company. Schneider-Kreuznach and Variogon are trademarks of Jos. Schneider Optische Werke GmbH used under license by Eastman Kodak Company. One Touch To Better Pictures not available for Macintosh computers. Product specifications subject to change without prior notice. Simulated LCD display image. IC-990 CAT No. 803 5669



Share Moments. Share Life.™

